




RoHS Compliant



N = Number of poles
Dim L=(N-1)x20.0+11.7
Dim P=(N-1)x20.0

Poles	Dim L	Dim P
2-4P	±0.15	±0.15
5-8P	±0.25	±0.25

Rev.	SIGN	DATE	DESCRIPTION	APPROVER
B		01/22'13	update the drawing	Da cheng
C	△	01/13'18	Upgrade the CULUS	Johnson

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ① Insulator(housing): Thermoplastic (UL94V-0)
- Item ② Wire guard: Stainless steel
- Item ③ Terminal Body(contact pin): Copper.Tin platd
- Item ④ Insulator(Cover): Thermoplastic (UL94V-0)
- Item ⑤ Pad board: Thermoplastic (UL94V-0)

Electrical: cULus

- Voltage rating: 600V
- Current rating: 57A
- Wire range(AWG): 6-24
- Wire strip length: 12-13mm
- Withstanding Voltage: 2.2KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval:
- Critical dimension: ▲

H8 xx 2 0 x 0 xxxx G

No. OF POLES
02: 2 POLES
:
08: 8 POLES

COLOR

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7004/P)
- 9 White(RAL1102)
- C: Multiple colors

RoHS compliant
(lead<4%)
In copper Alloy
0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

Amphenol
ANYTEK

INSPECTION COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	H8 20.0mm Series						
PART NO.	H8xx20x0xxxxG			DWG NO.	8H80103		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Johnson 2018.1.29	Johnson 2018.1.29		UNIT: mm		X. ±0.50
					SCALE: NONE		X.X ±0.30
					SHEET: 01/01		REV.: C
							X° ±1°