





RoHS Compliance



Poles	02	03	04	05	06	07	08	09	10	11	12	13
Dim L	10.10	15.10	20.10	25.10	30.10	35.10	40.10	45.10	50.10	55.10	60.10	65.10
Dim B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
TOL	± 0.15					± 0.20					± 0.25	
Poles	14	15	16	17	18	19	20	21	22	23	24	
Dim L	70.10	75.10	80.10	85.10	90.10	95.10	100.10	105.10	110.10	115.10	120.10	
Dim B	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.0	105.0	110.0	115.0	
TOL	± 0.25					± 0.30						



SECTION A-A

Rev.	SIGN	DATE	DESCRIPTION	APPROVER
B	△	11/21'09	The normal grey No. changed from RAL7004/P to RAL7035/D.	Kind
C	△	04/06'10	Add the 2P mark & Wire strip length is changed	RUNNER
D	△	10/12'11	Add "cULus" Safety Approval	Runner
E	△	02/25'19	Modify the drawing frame	Johnson
	△	02/25'19	Modify the Critical dimension	Johnson
	△	02/25'19	Add the Dimension $\phi 4.05^{+0.05}_{+0}$ mm	Johnson
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				

Material

- Item 1 Terminal top body: Thermoplastic (UL94V-0)
- Item 2 Terminal down body: Thermoplastic (UL94V-0)
- Item 3 Terminal lever: Thermoplastic (UL94V-0)
- Item 4 Wire guard: Stainless Steel
- Item 5 Female contact: PhBz (CuSn) Bright Tin plated

Electrical cULus

- Voltage rating: 300V
- Current rating: 10A
- Solid wire (AWG): 12-26
- Stranded wire (AWG): 12-26
- Wire strip length: 8-9mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval: cULus
- Critical dimension: △

HW xx 7 0 x 0 xxxx G

	Body color	
02 2 CONTACTS	0 Black (RAL9005)	0000 Standard @ Logo
03 3 CONTACTS	2 Red (RAL3001/D)	000A Standard ANY Logo (lead<4%)
...	3 Orange (RAL2011/P)	Any special item by
24 24 CONTACTS	5 Green (RAL6018/T)	customer request,
	6 Blue (RAL 5015/A)	please contact sales
	8 Grey (RAL7035/D)	department.
	9 White (RAL1102)	
	C Multiple colors	

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	HW 5.0 Series (W/O) contact on down side						
PART NO.	HWxx70x0xxxxG			DWG NO.	8HW0802		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Johnson 2019.02.25	Johnson 2019.02.25		UNIT: mm	X.	±0.50
					SCALE: NONE	X.X	±0.30
						X.XX	±0.10
				SHEET: 01/01	REV.: E	X°	±1°