





RoHS Compliant



N=NUMBER OF POLES

DIM		TOL		
		2×2P--2×6P	2×7P--2×12P	2×13P--2×16P
Dim A	(N/2-1)×3.5+5.0			
Dim B	(N/2-1)×3.5	±0.15	±0.20	±0.25
Dim P	(N/2-1)×3.5			

SIGN	DATE	DESCRIPTION	APPROVER
B	2019.11.07	The first release	Guoxue
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material:

- Item ① Terminal(housing): High temp. polyamide (UL94V-0)
- Item ② Contact pin : copper.tin plated

Electrical:

- Voltage rating: 160V
- Current rating: 5.5A
- Withstanding Voltage: 1.32 KV
- Operating temperature: -40°C to +110°C
- Reflow Soldering temperature: 260°C/10 Sec. Max.
- APPROVAL: 
- Critical dimension: 

KE xx 1 A x 0 xxxx G

No. OF POLES

04: 2×2 POLES

06: 2×3 POLES

⋮

32: 2×16 POLES

COLOR

0: BLACK

RoHS compliant
(lead<4%)
In copper Alloy

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark

Any special item by
customer request.
please contact sales
department.

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		KE 3.5mm W/O Flange Series (Vertical) THR type				
PART NO.		KExx1Ax0xxxxG		DWG NO.	8KE0427	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		Guoxue 2019.11.07	Guoxue 2019.11.07			
					SCALE: NONE	X.X ±0.30
					SHEET: 01/01	REV.: B
					X° ±1°	