




RoHS Compliant




SECTION P-P

N=Number of poles

Dim L	$(N-1) \times 3.50 + 4.9$
Dim B	$(N-1) \times 3.50$
Dim C	$(N-1) \times 3.50$

Poles	Dim B&Dim C	Dim L
2p	± 0.10	± 0.15
3p-6p	± 0.15	± 0.15
7p-12p	± 0.20	± 0.20
13p-16p	± 0.30	± 0.30



RECOMMENDED PCB LAYOUT

Rev.	SIGN	DATE	DESCRIPTION	APPROVER
B		2016.10.22	Initial Release	CHENMING
C		2020.07.29	Update reflow soldering temperature: 260°C±5°C/5 Sec	Devin

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ③ Male contact pin: Copper Bright Tin plated over Nickel plated
- Item ④ Terminal(housing): LCP (UL94V-0)

Electrical: cULus

- Voltage rating: 300V
- Current rating: 10A
- Withstanding Voltage: 1.6KV
- Operating temperature: -45°C to +130°C
- Reflow soldering temperature: 260°C±5°C/5 Sec.
- Safety Approval:

OQ xx 1 G 0 1 Bxxx G

No. OF POLES
02: 2 POLES
03: 3 POLES
:
:
16: 16 POLES

0 Black (RAL9005)

G RoHS compliant
(lead<4%)
In copper Alloy

B000: "@" Logo (Standard)
B00A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		OQ 3.50mm 90° Series Close THR				
PART NO.	OQxx1G01BxxxG			DWG NO.	80Q0C30	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		Devin 2020.07.29	Devin 2020.07.29		UNIT: mm	X. ±0.50
					SCALE: NONE	X.X ±0.30
				SHEET: 01/01	REV.: C	X.XX ±0.10
						X° ±1°