

	1	2		3		4		5			6		7	
ROHS	Compliant													
Е														Е
	Product	requireme	ent a.											
		s: PA6 45%GF					Quality o	control r	equiremen	nts				
	材质: PA	N6 45%GF , 半	-透明				1. Measur	ements o	f three	serial	ized par	ts, from ea	nch cavity,	,
		ıd parting li ·模线不超过0.		shall not ex	ceed 0.05mm		for all o	ther par	ameters/	dimensi	ons deno	ted on the		
	3. All fill	ets and radi	ii shall be F	RO.2mm and al		1e	Marked"▲ 每穴取5P(					尺十		
				otherwise spe 则为准,未注拔			4)(-1001)	~ 11 66 15% 3		43 44.54	- // ± ///	, 1		
D		女因用NO.2不 it warpage is			/ 大川 / 人									D
		度不超过0.2m												
		10u1a be clea ·净,无杂质.	in and free f	orm impuriti	es									
	6. Outside	surface of p		nooth and fre		scratche	S,							
		ks or other b :面应光滑,无		less otherwis i水 污渍	se specified									
	7. Ejector	pads shall n	not exceed 0.	05mm above o	or below the	parts su	rface							
		出或凹陷不超		1 4 - 0 2	1 41		C.							
		Diection snai L应在产品表面		1 to 0.2mm ma	ix above the	parts su	rraces							C
	<i>7</i> 1													
В														В
_								<u>Amp</u>	hen	ol			СОРҮ	_
									NYTE		THIRD PARTIES	ERVED. REPRODUCTION IN ANY FORM WHATEVER OUT WRITTEN AUTHORITY	IS NOT	
							TITL		dle for HO			OPERTY OF ANYTEK TECH		$\dashv$
A							PART		x00000G		DWG NO.	AB1001		
11							APPRO'	/ED CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance   X. ± 0.20	$\prod^{\Lambda}$
									Johnson	Johnson	⊕ €	UNIT: mm SCALE: 4:1	X. X ±0.10 X. XX ±0.05	
	1	2		3		4		5	2019. 08. 23	2019. 08. 23	SHEET: 2 /2	REV.: B	7 x ±1°	