







N=Number of poles

Dim L	$(N-1) \times 3.81 + 5.0$
Dim B	$(N-1) \times 3.81$
Dim C	$(N-1) \times 3.81$

Poles	Dim B & Dim C	Dim L
2p	± 0.10	± 0.15
3p-6p	± 0.15	± 0.15
7p-12p	± 0.20	± 0.20
13p-16p	± 0.30	± 0.30



SECTION P-P



RECOMMENDED PCB LAYOUT

SIGN	DATE	DESCRIPTION	APPROVER
Δ			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ③ Male contact pin: Copper , Bright Tin plated over Nickel plated
- Item ④ Terminalhousing: LCP (UL94V-0)

Electrical:

cULus

- Voltage rating: 300V
- Current rating: 10A
- Withstanding Voltage: 1.6 KV
- Operating temperature: -45°C to $+130^{\circ}\text{C}$
- Reflow soldering temperature: $260^{\circ}\text{C}/10$ Sec max
- Safety Approval: cULus

OQ xx 3 G x 1 Bxxx G

No. OF POLES

02: 2 POLES

03: 3 POLES

...

16: 16 POLES

Color

0 Black (RAL9005)

G RoHS compliant
(lead<4%)
In copper Alloy

B000: "@" Logo (Standard)

B00A: "ANYTEK" Mark

Any special item by
customer request.
please contact sales
department.

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	OQ 3.81mm 90° Series 2P-16P Close THR (Tape reel)						
PART NO.	OQxx3Gx1BxxxG			DWG NO.	80Q0F07		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			
		CHENMING 2016.12.14	CHENMING 2016.12.14		UNIT: mm	Tolerance	
					SCALE: NONE	X. ± 0.50	
						X.X ± 0.30	
						X.XX ± 0.10	
						X° $\pm 1^{\circ}$	
				SHEET: 01/01	REV.: B		