

REV	SIGN	DATE	DESCRIPTION	APPROVER
B		2011.09.24	New release	Runner
C	△	2017.11.28	update the drawing	Zhihua
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				

Material:

- Item ① Insulator(Cover): Thermoplastic (UL94 V-0)
- Item ② Insulator(housing): Thermoplastic (UL94 V-0)
- Item ③ Spring clamp: Stainless steel
- Item ④ Terminal Body(contact pin): Brass, Tin plated

Electrical: cULus

- Voltage rating: 300V
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 12-28
- Stranded wire(AWG): 12-28
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec △
- Critical dimension: ▲
- Safety Approval: cULus

HS xx 5 0 x 1 xxxx G

No. OF POLES

08: 4×2 POLES
60: 4×15 POLES
64: 4×16 POLES

COLOR

0: BLACK
5: GREEN (RAL 6018/T)
6: BLUE
8: GREY (RAL 7004/P)

G RoHS compliant △
(lead<4%)
In copper Alloy





0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		HS 7.62mm Series (Solder pins staggered by half the pin spacing)			
PART NO.	HSxx50x1xxxxG			DWG NO.	8HS0005
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Zhihua 2017.11.28	Zhihua 2017.11.28		Tolerance
					X. ±0.50
					X.X ±0.30
					X.XX ±0.10
					X° ±1°
				SHEET: 01/01	REV.: C



△

N = Number of poles.
Dim.A = N*7.62-1.54
Dim.B = (N-1)*7.62

POLE	4×2 ~ 4×4	4×5 ~ 4×8	4×9 ~ 4×12	4×12 ~ 4×16
Dim.A	±0.15	±0.25	±0.35	±0.45
Dim.B	±0.15	±0.25	±0.30	±0.40