





RoHS Compliant



Rev	SIGN	DATE	DESCRIPTION	APPROVER
C	△	2009.07.17	Add the inspection dimension	Jacke
D	△	2010.05.29	Add cULus standard	Jacke
E	△	2024.06.03	Update the drawing, Add the inspection dimension	PansLee

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item a Terminal(housing): PA66 (UL 94 - V0)
- Item b Male contact pin: Copper Tin plated
- Item c Wire guard: Stainless Steel
- Item d With flange nut : Steel zinc plated M3

Electrical: cULus IEC

- Voltage rating: 300V 1000V
- Current rating: 55A 76A
- Withstanding Voltage: 1.6 KV
- Rated impulse voltage: 8 KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval: cULus

- △ Critical dimension: △

PART NO.

KL xx 62 x 1 xxxx G

No. OF POLES
02 2 CONTACTS
03 3 CONTACTS
...
12 12 CONTACTS

Color
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)

△ RoHS compliant (lead<4%)
In copper Alloy
0000: "△" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	38.08	48.24	58.40	68.56	78.72	88.88	99.04	109.20	119.36	129.52	139.68
Dim B	10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76
TOL	±0.25					±0.35					

Amphenol
ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	KL 10.16 Series 2p-12p Right -Angle with flange (down)									
PART NO.	KLxx62x1xxxxG				DWG NO.	8KL0004				
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.				Tolerance		
		PansLee 2024.06.03	PansLee 2024.06.03					X.	±0.50	
								X.X	±0.30	
								X.XX	±0.10	
								X°	±1°	