



SIGN	DATE	DESCRIPTION	APPROVER
△	2010.10.23	Add UL standard	Jacke
△	2010.10.23	The material is changed from Brass to copper	Jacke
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			




Material

- ▲ ●Item@aMale contact pin: Copper,Tin plated.
- Item@bTerminal (housing): PA66 30%GF(UL94V-0)
- Item@cwith flange nut: Brass ,Ni plated. M2.0

Electrical cULus / IEC

- Voltage rating: 300V/160V
- Current rating: 10A/13A
- Withstanding Voltage: 1.6KV/2.5KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C±10°C/5 Sec

-
 ● Safety Approval:



RECOMMENDED PCB LAYOUT

EL xx 15 x 3 xxxx G

- | | |
|-----|----------|
| 02 | 2 POLES |
| 03 | 3 POLES |
| ... | ... |
| 24 | 24 POLES |

Pb < 40,000ppm
(RoHS)

000 0 @ Logo
000 A ANY Logo
Any special item by
customer request,
please contact sales
department.

Color

- 0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)

Poles	2p	3p	4p	5p	6p	7p	8p	9p	10p	11p	12p	13p
Dim L	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0	45.5	49.0	52.5
Dim B	3.50	7.00	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
TOL	±0.15					±0.20						±0.25
Poles	14p	15p	16p	17p	18p	19p	20p	21p	22p	23p	24p	
Dim L	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5	84.0	87.5	91.0	
Dim B	45.5	49.0	52.5	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5	
TOL	±0.25					±0.30						

ANYTEK				CUSTOMER COPY ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD			
TITLE		EL 3.5mm Right angle with flange Dip TYPE Series					
PART NO.		ELxx15x3xxxx G		DWG NO.		8EL0104	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Jacke 2010.10.23	Jacke 2010.10.23			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
					UNIT: mm SCALE: NONE SHEET: 01/01		REV.: C