




RoHS Compliant

Rev.	SIGN	DATE	DESCRIPTION	APPROVER
B	—	2019.10.16	The first release	Guoxue
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				



Material

- Item③Male contact pin: Copper,Tin plated.
- Item④Terminal (housing): High temp. polyamide (UL94V-0)
- Item⑤with flange nut: Brass ,Ni plated. M2.0

Electrical cULus

- Voltage rating: 300V
- Current rating: 10A
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +130°C
- Reflow Soldering temperature: 260°C/10 Sec Max.
- Safety Approval:
- Critical dimension:

EL xx 15 x B xxxx G

02 2 POLES
03 3 POLES
...
24 24 POLES

Color
0 Black (RAL9005)

RoHS compliant (lead<4%)
In copper Alloy

000 0 @ Logo
000 A ANY Logo
Any special item by customer request, please contact sales department.

Poles	2p	3p	4p	5p	6p	7p	8p	9p	10p	11p	12p	13p
Dim L	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0	45.5	49.0	52.5
Dim B	3.50	7.00	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0
TOL	±0.15					±0.20					±0.25	
Poles	14p	15p	16p	17p	18p	19p	20p	21p	22p	23p	24p	
Dim L	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5	84.0	87.5	91.0	
Dim B	45.5	49.0	52.5	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5	
TOL	±0.25					±0.30						

Amphenol ANYTEK					CUSTOMER COPY ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD				
TITLE		EL 3.5mm Right angle SMT TYPE Series							
PART NO.		ELxx15xBxxxx G			DWG NO.		8EL0008		
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance		
			Guoxue 2019.10.16	Guoxue 2019.10.16		UNIT: mm		X.	±0.50
						SCALE: NONE		X.X	±0.30
								X.XX	±0.10
						SHEET: 01/01		REV.: B	X°