


RoHS Compliant

No. OF POLES
04: 4 POLES

KX 04 C 1 x 2 xxxx G

G RoHS compliant
(lead<4%)
In copper Alloy

COLOR

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)
- 9 White(RAL1102)
- C Green(RAL6018/U)

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

REV	SIGN	DATE	DESCRIPTION	APPROVER
B		05/03-11	Initial release	Runner
C	△	05/13-20	Add RoHS Compliant, and Amphenol Logo	Chen Bo
	△	05/13-20	Change the symbol of critical dimension	Chen Bo
	△	05/13-20	add cULus safety certification mark	Chen Bo
	△	05/13-20	add the colour code, change the torque force	Chen Bo



THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item A Terminal housing: Thermoplastic (UL94V-0)
- Item B Terminal cover: Thermoplastic (UL94V-0)
- Item C Female contact : Copper. Tin plated
- Item D Wire guard : Stainless Steel
- Item E Clamp : Steel Stamping , Zinc plated
- Item F Handle: Steel t=1.5mm, Zinc plated
- Item G Terminal screw: Zinc plating"-slot type,M5
- Item H With flange screw: Zinc plating"*slot type,M5

Electrical: cULus

- Voltage rating: 600 V
- Current rating: 115 A
- Wire range:
- Solid wire(AWG): 2-20
- Stranded wire(AWG): 2-20
- Torque(Lb-In): 31.5 (The maximum allowable torque is 36.5Lb-In)
- Screw: M5
- Wire strip length: 19-20mm
- Withstanding Voltage: 2.2 KV
- Operating temperature: -40°C to +115°C
- APPROVAL: cULus
- △ Critical dimension: ▲

**Amphenol**
ANYTEK**CUSTOMER COPY**ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY
FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE
PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		KX 15.0mm Series (with handle) 4P				
PART NO.	KX04C1x2xxxxG			DWG NO.	8KX0002	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		Chen Bo 05/13-20	Chen Bo 05/13-20		UNIT: mm	X. ±0.50
					SCALE: NONE	X.X ±0.30
						X.XX ±0.10
				SHEET: 01/01	REV.: C	X° ±1°