





RoHS Compliant

P.C.B Layout
Top view

SECTION 0-0

N=Number of contacts

Dim A	$(N/2-1) \times 3.5 + 4.3$
Dim B	$(N/2-1) \times 3.5$
Dim C	$(N/2-1) \times 3.5$

POLES	Dim. Tol	Dim. A/B
2x2p-2x6p		± 0.15
2x7p-2x12p		± 0.25
2x13p-2x20p		± 0.30

REV	SIGN	DATE	DESCRIPTION	APPROVER
B		10/30-19	Initial release	Chen Bo
C	△	12/16-19	Add the cULus safety parameters	Chen Bo
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				

Material:

- Item ② Terminal housing: LCP (UL94V-0)
- Item ③ Male contact short pin: Copper, Bright Tin plated over Nickel plated
- Item ④ Male contact long pin: Copper, Bright Tin plated over Nickel plated
- Item ⑤ cover plate: LCP (UL94V-0)

Electrical: cULus

- Voltage rating: 150V
- Current rating: 8A
- Withstanding Voltage: 1.3KV
- Operating temperature: -40°C to $+130^{\circ}\text{C}$
- Reflow soldering temperature: $260^{\circ}\text{C}/10$ Sec max
- Safety Approval: cULus
- Critical dimension: ▲
- Reference dimension: (×) The dimensions of pitch are just for reference, take the actual assembly result as a judgment when inserting the terminal block into the PCB hole.

NR xx 1 C x 1 xxxx G

No. OF POLES
04: 2x2 POLES
06: 2x3 POLES
:
:
40: 2x20 POLES

COLOR
0: BLACK

RoHS compliant
(lead<4%)
In copper Alloy
0000: "②" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by
customer request.
please contact sales
department.

Amphenol
ANYTEK**CUSTOMER COPY**

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		NR 3.5mm B type 90° W/o Flange Series(THR)			
PART NO.	NRxx1Cx1xxxxG			DWG NO.	8NR0102
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Chen Bo 12/16-19	Chen Bo 06/03-19		Tolerance
					X. ± 0.50
					X.X ± 0.30
					X.XX ± 0.10
					X° $\pm 1^{\circ}$
SHEET: 01/01		REV.: C			