

N = Number of poles  
Dim A = N x 5.0  
Dim B = (N - 1) x 5.0



poles	Dim A	Dim B
2p	±0.15	±0.10
3P-8p	±0.15	±0.15
9P-12p	±0.20	±0.20
13P-18p	±0.30	±0.30
19P-24p	±0.40	±0.40

REV	SIGN	DATE	DESCRIPTION	APPROVER
C	△	6/24'06	Torque standard is changed from 3.5Lb-In to 1.7Lb-In	Marvin
D	△	10/04'06	The structure is changed	Marvin
E	△	2009.08.25	Add the tolerance table	Jacke
	△	2009.08.25	The Operating temperature is changed	Jacke
	△	2009.08.25	Poles are changed from 2-24P to 4-24P.	Jacke
F	△	06/26-23	Poles are changed from 4-24P to 2-24P.	Chen Bo

### Material

- Item a Clamp: Brass(CuZn) Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact: PhBz, Gold plating 1~3u" on the contact area, Ni plated on other area.
- Item d Terminal (housing): Thermoplastic (UL94V-0)
- Item e Terminal (cover): Thermoplastic (UL94V-0)

### Electrical

- Voltage rating: 300V
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 16-22
- Stranded wire(AWG): 16-22
- Torque(Lb-In): 1.7
- Screw: M3
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Safety Approval:  US
- Critical dimension: 

TT xx 01 x 1 xxxx G

02 2 CONTACTS  
03 3 CONTACTS  
...  
24 24 CONTACTS


Color  
0 Black (RAL9005)  
2 Red (RAL3001/D)  
3 Orange(RAL2011/P)  
4 Yellow(RAL1018/A)  
5 Green(RAL6018/T)  
6 Blue (RAL5015/A)  
8 Grey(RAL7035/D)  
9 White(RAL1102)

G RoHS compliant  
(lead<4%)  
In copper Alloy  
0000 Standard @ Logo  
000A Standard ANY Logo  
Any special item by  
customer request,  
please contact sales  
department.

**Amphenol**  
**ANYTEK**

### CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		TT - 5.0mm Series Solid block			
PART NO.	TTxx01x1xxxxG			DWG NO.	8TT0301
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Chen Bo 06/26-23	Jacke 2009.08.25		
SHEET: 01/01				UNIT: mm	X. ±0.50
				SCALE: NONE	X.X ±0.30
				REV.: F	X.XX ±0.10
					X° ±1°