




SIGN	DATE	DESCRIPTION	APPROVER
△	2010.12.20	The design is changed	Chen Bo
△	07/29'11	The torque is changed & Add is the "cULus" mark	Runner
△	07/29'11	The voltage rating is changed from 600V to 300V	Runner
△	07/29'11	The withstanding voltage is changed from 2.2KV to 1.6KV	Runner
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

- Material:
- Item a Terminal housing :Thermoplastic (UL 94V-0)
 - Item b Clamp : Brass, Ni plated.
 - Item c Wire guard solder pin (Front single row) : Copper , Tin plated
 - Item d Terminal screw: Steel Zinc plating"-slot type
- Electrical
- △ ● Voltage rating : 300V
 - Current rating : 65A
 - Wire range :
 - Solid wire (AWG) : 6-20
 - Stranded wire (AWG) : 6-20
 - △ ● Torque (LB-In.) : 12.2
 - Screw : M4.5
 - △ ● Wire strip length : 10~11mm
 - △ ● Withstanding voltage : 1.6KV
 - Operating temperature : -40°C+115°C
 - Soldering temperature : 250°C+10°C/5 Sec
 - △ ● Critical dimension: US
 - Safety Approval:

KP xx 2 1 x 2 xxxx G

RoHS
Pb<40,000ppm

02 2 Poles
03 3 Poles
...
12 12 Poles

Color

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)

0000:"@Logo (Standard)
000A:"ANYTEK"Logo
Any special item by customer request, please contact sales department.

Poles	01	02	03	04	05	06	07	08	09	10	11	12
Dim L	10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76	121.92
Dim B		10.16	20.32	30.48	40.64	50.80	60.96	71.12	81.28	91.44	101.60	111.76
TOL	±0.10	±0.20			±0.30				±0.40			

ANYTEK

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

CUSTOMER COPY

TITLE				KP 10.16 Series Front single row (Without cover)			
PART NO.		KPxx21x2xxxxG		DWG NO.		8KP0103	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance
			Runner 2011.07.29	Chen Bo 2010.12.20			X. ±0.50 X.X ±0.30 X.XX ±0.10 X° ±1°
					SHEET: 01/01		REV.: D