



Poles	02	03	04	05	06	07	08	09	10	11	12	13
Dim L	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00	65.00
Dim B	5.00	10.00	15.00	20.00	25.00	30.00	35.00	40.00	45.00	50.00	55.00	60.00
TOL	±0.15					±0.20						±0.25
Poles	14	15	16	17	18	19	20	21	22	23	24	
Dim L	70.00	75.00	80.00	85.00	90.00	95.00	100.0	105.0	110.0	115.0	120.0	
Dim B	65.00	70.00	75.00	80.00	85.00	90.00	95.00	100.0	105.0	110.0	115.0	
TOL	±0.25					±0.30						

SIGN	DATE	DESCRIPTION	APPROVER
	05/20.08	change the structure	Aaron
	05/20.08	Add the cULus	Aaron
	07/14.14	update the drawing	Guoxue

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item Ⓐ Terminal cover : Thermoplastic (UL94V-0)
- Item Ⓑ Terminal housing : Thermoplastic (UL94V-0)
- Item Ⓒ Terminal screw : Steel Zinc plating "-" slot type
- Item Ⓓ Wire guard solder pin : Brass, Tin plated
- Item Ⓔ Clamp : Steel stamping, Zinc plating

Electrical cULus

- Voltage rating: 300VAC
 - Current rating: 10A
 - Wire range:
 - Solid wire(AWG): 12-22
 - Stranded wire(AWG): 12-22
 - Torque(Lb-In): 3.5
 - Screw: M2.5
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Soldering temperature: 260°C±5°C/5 Sec
 - Safety Approval:  US
- Critical dimension:
PART NO.

△ EQ xx 05 x 1 xxxx G

RoHS compliant
(lead<4%)
In copper Alloy

Poles
02 2 Poles
03 3 Poles
.....
24 24 Poles

Color

0	Black (RAL9005)
2	Red (RAL3001/D)
3	Orange(RAL2011/P)
4	Yellow(RAL1018/A)
5	Green(RAL6018/T)
6	Blue (RAL5015/A)
8	Gray(RAL7035/D)
C	Green(RAL6018/U)

0000 Standard @ Logo
000A Standard ANY Logo
Any special item by
customer request,
please contact sales
department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	EQ 5.0 Series 180 D Wire inlet (Horizontal)						
PART NO.	EQxx05x1xxxxG			DWG NO.	8EQ0001		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance
		Guoxue 2014.07.14	Guoxue 2014.07.14		UNIT: mm	X.	±0.50
					SCALE: NONE	X.X	±0.30
					SHEET: 01/01	X.XX	±0.10
					REV.: D	X*	±1*