

Material		
● Item 1	Insulating body	Thermoplastic (UL94V-0)
● Item 2	Insulating cover	Thermoplastic (UL94V-0)
● Item 3	Insulating partition	Thermoplastic (UL94V-0)
● Item 4	Contact on entry pin	Brass, Tin plated
● Item 5	Contact on back pin	Brass, Tin plated
● Item 6	Spring clamp	Stainless steel

Electrical **cULus**

- Voltage rating: 300VAC
- Current rating: 8A
- Wire range:
- Solid wire(AWG): 16-20
- Stranded wire(AWG): 16-20
- Wire strip length: 7-8mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval: us
- Critical dimension: 

▲ No. OF POLES
02: 2 POLES
04: 4 POLES
06: 6 POLES
:
12: 12 POLES

- A Body Color
 0 Black (RAL9005)
 1 Red (RAL3001/D)
 2 Orange (RAL2011/P)
 3 Yellow (RAL1018/A)
 4 Green (RAL6018/T)
 5 Blue (RAL5015/A)
 6 Grey (RAL7004/P)
 7 White (RAL102)
 C Multiple colors
- 0000 Standard @ Logo
 000A Standard ANY Logo
 Any special item by
 customer request,
 please contact sales
 department.

RoHS compliant
(lead & Cd free)
In copper Alloy

2013.12.26

發行

發 行
INTERNATIONAL CO., LTD.

ΔN=NUMBER OF POLES

Dim L	$N \times 7.5 - 0.5$
Dim B	$(N-1) \times 7.5$

	POLES	Dim L	Dim B
Δ	2p-8p	± 0.20	± 0.20
	10p-12p	± 0.30	± 0.30

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		H7 7.5 Series Double row the 1st pole with side contact (雙排P)					
PART NO.		H7xx10x3xxxxG		DWG NO.		8H70010	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
		Da cheng 2013.12.17	Da cheng 2013.12.17		UNIT: mm	X.	±0.50
					SCALE: NONE	X.X	±0.30
						X.XX	±0.10
SHEET: 01/01				REV: 0		X'	±1