






RoHS Compliant



PCB Layout (TOP VIEW)



the first pin

P=NUMBER OF CONTACTS

DIM		TOL		
		1P	2P	3P-4P
Dim A	6.35×P+1.8	±0.20	±0.30	±0.40
Dim B	6.35×(P-1)	/	±0.30	±0.40
DIM		TOL		
		5P-8P	9P-12P	13P-16P
Dim A	6.35×P+1.8	±0.50	±0.60	±0.80
Dim B	6.35×(P-1)	±0.50	±0.60	±0.80

REV	SIGN	DATE	DESCRIPTION	APPROVER
B		2020.11.04	Initial release	Devin
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!				

Material:

- Item ① Cover: Thermoplastic (UL 94V-0)
- Item ② Housing: Thermoplastic (UL 94V-0)
- Item ③ Side Cover: Thermoplastic (UL 94V-0)
- Item ④ Spring clamp: Stainless steel
- Item ⑤ Back Contact: Copper, Tin plated over Nickel plated
- Item ⑥ Front Contact: Copper, Tin plated over Nickel plated

Electrical:	cULus	VDE
● Voltage rating:	600V	1000V
● Current rating:	30A	41A
● Wire range:		
● Solid wire(AWG):	10-24	6-0.5mm ²
● Stranded wire(AWG):	10-24	6-1.0mm ²
● Wire strip length:	11-12mm	
● Withstanding Voltage:	2.2KV	
● Operating temperature:	-40°C to +120°C	
● Soldering temperature:	260°C±5°C/5 Sec	
● Safety Approval:	cULus	
● Critical dimension:	▲	

No. OF POLES	XA XX 1.0 X 0 XXXX G	Pitch	1 6.35	RoHS compliant (lead<4%) In copper Alloy
01 1 CONTACTS				
02 2 CONTACTS				
...				
12 12 CONTACTS				
Body	Color			
0 Black (RAL9005)				0000: "@" Logo (Standard)
1 Nature Color				000A: "ANYTEK" Mark
2 Red (RAL3001/D)				
3 Orange(RAL2011/P)				
4 Yellow(RAL1018/A)				
5 Green(RAL6018/T)				
6 Blue (RAL5015/A)				
7 Brown				
8 Grey(RAL7004/P)				
9 White(RAL1102)				

Amphenol
ANYTEK

INSPECTION COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	XA 6.35mm Series				
PART NO.	XAxx10x0xxxxG			DWG NO.	8XA0001
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
		Devin 2020.11.04	Devin 2020.11.04		X. ±0.50
					X.X ±0.30
					X.XX ±0.10
					X° ±1°
				SHEET: 01/01	UNIT: mm
					SCALE: 2:1
					REV.: B