



DIMENSION

Dim L	Nx5.0
Dim B	(N-1)x5.0

N=Number of contacts

Poles	B Tolerance	L Tolerance
4pole~6pole	± 0.15	± 0.15
7pole~12pole	± 0.25	± 0.25
13pole~18pole	± 0.35	± 0.35
19pole~24pole	± 0.40	± 0.40

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			
△			

Material:

- Item 1 Terminal housing: Thermoplastic (UL 94V-0)
- Item 2 Clamp: Brass ,Ni plated
- Item 3 Wire guard solder pin: Brass ,Tin plated
- Item 4 Terminal screw: Steel , Zinc plating"-slot type

Electrical

- Voltage rating: 300VAC
- Current rating: 10A
- Wire range:
- Solid wire(AWG): 12-24
- Stranded wire(AWG): 12-24
- Torque(Lb-In): 3.5
- Screw: M2.5
- Wire strip length: 6-7mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to $+115^{\circ}\text{C}$
- Soldering temperature: $250^{\circ}\text{C} \pm 10^{\circ}\text{C}/5 \text{ Sec}$

YE xx 01 x 1 xxxx G

04 4 CONTACTS	0 Black	0000:"@Logo (Standard)	Pb < 40,000ppm (RoHS)
05 5 CONTACTS	5 Green	000A:"ANYTEK"Logo	
... ..	6 Blue	Any special item by	
24 24 CONTACTS	8 Grey	customer request,	
		please contact sales	
		department.	

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	YE-5.0mm Series 4P-24P (Solid block)						
PART NO.	YExx01x1xxxxG			DWG NO.	8YE0007		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Aaron 2009.10.07	Aaron 2009.10.07			UNIT: mm	X. ± 0.50
						SCALE: NONE	X.X ± 0.30
						REV.: B	X.XX ± 0.10
					SHEET: 01/01		X° $\pm 1^{\circ}$